

DOOR & WINDOW GASKETS

Dies & molds designed and produced on site.

Available on reels or cut and molded to specifications.

Gaskets meet RMA Class 2 tolerances.



Central Sales & Service, Inc. specializes in the design and manufacture of door and window gaskets for the transportation market.

We produce all sizes from small pound-in gaskets to large tires using FRA smoke and flame certified neoprene and 60, 70, 80 duromter EPDM.

Lead time from design to FAI is generally six weeks, including water-tight testing. Gaskets can be manufactured

> with vulcanized splices, injected corner seams or extruded onto reels.

Filler strips with molded pull handles manufacutured in black or red.

Accepted drawing formats include pdf, dwg and dxf.




Table 16. Cut Length tolerance for unspliced extrusion				
RMA Class		1 - High Precision	2 - Precision	3 - Commercial
Length (in Inches)				
Above	Up to			
0	1.6	0.03	0.04	0.06
1.6	2.5	0.03	0.05	0.08
2.5	4	0.04	0.06	0.1
4	6.3	0.05	0.08	0.13
6.3	10	0.06	0.1	0.16
10	16	0.8	0.13	0.2
16	25	0.1	0.16	0.25
25	40	0.13	0.2	0.4
40	63	0.16	0.25	0.5
63	100	0.2	0.4	0.63
100	160	0.25	0.5	0.8
160		0.16%	0.32%	0.50%



110 Industrial Court Waverly, TN 37185 Toll Free 800.467.0568 Ph. 931.296.1940 Fax 931.296.1944

www.centralsales-service.com